## (19) World Intellectual Property **Organization**

International Bureau



# 

(43) International Publication Date 14 July 2005 (14.07.2005)

**PCT** 

### (10) International Publication Number WO 2005/063558 A1

(51) International Patent Classification<sup>7</sup>:

B62K 11/14

(21) International Application Number:

PCT/SE2004/001971

(22) International Filing Date:

22 December 2004 (22.12.2004)

(25) Filing Language:

Swedish

(26) Publication Language:

English


(30) Priority Data: 0303589-6

30 December 2003 (30.12.2003) SE

- (71) Applicant and
- (72) Inventor: NORRMAN, Jan [SE/SE]; Ytterbyvik 3, S-185 94 Vaxholm (SE).
- (74) Agents: SUNDSTRÖM, Per et al.; Stenhagen Patentbyrå AB, P.O. Box 4630, S-116 91 Stockholm (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

#### (54) Title: A CONTROL DEVICE FOR A MOTOR VEHICLE



(57) Abstract: An automotive vehicle, such as a motorcycle, has an electric ignition system for igniting fuel delivered to the engine of the vehicle, and a rotatable handle which the driver holds in one hand when driving the vehicle and rotates to control the power output of the engine between an idling end position and a high power end position. The device includes a switch (80) for cutting out the ignition system (72) temporarily. This is achieved by turning the handle (2) towards and beyond a yieldable engine-idling abutment (63), by exerting a strong torque that exceeds a pre-chosen value.

## WO 2005/063558 A1



#### Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

#### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.